



RECORDING APPARATUS AND RECORDING METHOD OF  
ELECTRONIC WATERMARK

BACKGROUND OF THE INVENTION

5

Field of the Invention:

The present invention relates to a recording of contents information recorded with an electronic watermark signal therein, particularly, relates to a recording apparatus and a recording method of an electronic watermark, wherein an electronic watermark signal is always held when a part of contents information is extracted and recorded.

15 Description of the Related Art:

An electronic watermark is a technique of embedding a certain information in a multimedia data such as image and sound and concealing the certain information. There provided various methods of concealing.

20 The NTT Human Interface Laboratory reported "An Embedding Method of Copyright Information using DCT for Digital Moving Pictures" in the SCIS'97-31G. It proposes the method of embedding information in the MPEG (Moving Picture Experts Group) code, particularly, the method of embedding information based upon alteration of DCT (discrete cosine transform) coefficient, a motion vector and quantization characteristics.

The Defense Academy of Japan reported "A Method of

000090-09726560  
Sub  
9/1

Signing Watermark on a Picture by PN Succession" in the SCIS'97-26B. It proposes the method of diffusing a picture signal by the PN succession and synthesizing a signature information with the picture in accordance with the direct diffusion method.

5 G. Caronni proposed that a tag, which is a small geometrical pattern, was added to an electronically processed picture in an intensity level, which is hardly perceived visibly, is proposed in the thesis titled "Assuring Ownership Rights for Digital Images" in the Proc. Reliable IT Systems, VIS'95, 1995. A method of  
10 embedding an electronic watermark signal, which is resemble to quantization noise is described in the theses "Embedding Secret Information into a Dithered Multi-level Image" in the IEEE Military Comm. Conference, pp. 216-220, 1990 by K. Tanaka and "Video-steganography" in the IMA Intellectual Property Proc., VI,  
15 pp. 187-206, 1994 by K. Mitsui et al. respectively.

A method of inserting an electronic watermark signal into a pixel allocated in a vicinity of an outline of picture in the least significant bit is described in the thesis titled "Cryptology for Digital TV Broadcasting", Proc. of the IEEE, 83(6), pp. 944-957,  
20 1995, by Macq and Quisquater.

A statistical method called "patchwork" and a method of utilizing a random texture pattern, which is shown in a picture called "texture block coding" is explained in the thesis titled "Techniques for Data Hiding", Proc. of SPIE, v2420, page 40, July  
25 1995, by W. Bender et al.

MPEG signal, which is one of compressed signals, to be inserted with an electronic watermark signal is depicted next. Essentially MPEG is a name of organization, "Moving Picture

Experts Group". However, it currently represents standards or specifications for coding signals. Accordingly, MPEG is composed of several techniques.

Fig. 6 shows a block diagram of the MPEG encoder according to the prior art.

In Fig. 6, the MPEG encoder comprises a predictor 41 for motion compensation, a subtracter 42, a discrete cosine transformer (DCT) 43, a quantizer 44, a VLC (variable length coder) 45, a buffer 46, an inverse-quantizer 47, an inverse-DCT 48, an adder 49 and a memory 50 for picture.

In the subtracter 42, a difference between an input picture signal and a locally decoded picture, which is predicted for motion compensation by the predictor 41, is subtracted from the input picture signal. Accordingly, a time redundancy portion is deleted from the input picture signal. There exist 3 modes of predicting directions: "past", "future" and "both past and future". Further, these modes can be used by switching each macro block (MB) of 16 pixels multiplied by 16 pixels. A direction of prediction is decided by a picture-type given to the input picture signal. There is existed 2 modes of "predicting from past" and "encoding an MB independently without predicting" in a predictive coded picture (P-picture). There is existed 4 modes of predicting "future", "past", "both past and future" and "encoding a MB independently without predicting" in a bi-directionally predictive coded picture (B-picture). Furthermore, encoding all MBs independently is an intra-coded picture (I-picture).

A motion vector is detected with the accuracy of half pel or half-pixel after performing a pattern matching of a motion area at

000290-051-0500  
Sub  
A5

Sub  
A6

each MB and motion compensation is predicted by shifting it with a motion component. There is existed 2 directions of horizontal and vertical in a motion vector. The direction is transmitted as an additional information of MB in conjunction with a motion compensation (MC) mode, which indicates a prediction from where. From a first I-picture to a picture preceding a second I-picture is called a group of pictures (GOP). In a case that the GOP is used in storage media such as an optical recording medium and a magnetic recording medium, approximately 15 pictures are used in general.

A differential picture is orthogonally transformed in the DCT 43. According to MPEG, the 2-dimensional DCT is applied to a DCT block of 8×8 with dividing one MB into 4. Generally, a video signal contains more low frequency components and less high frequency components, so that DCT coefficients converge into low frequency components if the DCT is applied.

The picture data (DCT coefficient) applied by the DCT is quantized by the quantizer 44.

The quantized data is processed with the variable length coding (VLC) by the VLC 45.

The data coded by VLC is temporarily stored in the buffer 46 and outputted as a coded data in a predetermined transfer rate. A generated coding amount per MB of the data to be outputted is transferred to a code amount limiter not shown. The code amount limiter controls a quantizing scale by feeding an error code amount, which is a difference between the generated code amount and a target code amount, back to the quantizer 44 for controlling the generated code amount.

Further, the quantized picture data is inversely quantized by

the inverse-quantizer 47 and inversely discrete cosine transformed by the inverse-DCT 48 and temporarily stored in the memory 50 through the adder 49, and then the quantized picture data is used in the predictor 41 for motion compensation as reference of a decoding picture or a local decoding picture so as to calculate a differential picture.

The coded data outputted from the buffer 46 is decoded through an inverse process of coding.

Fig. 7 shows a block diagram of the MPEG decoder according to the prior art.

In Fig. 7, the MPEG decoder comprises a variable length decoder (VLD) 51, an inverse-quantizer 52, an inverse-DCT 53, an adder 54, a memory 55 for a picture and a predictor 56 for motion compensation.

With respect to an insertion frequency of electronic watermark signals in the prior art mentioned above, it almost depends upon an application. For example, in a case of picture data, electronic watermark signals are scattered by using several frames of pictures with depending upon a method of electronic watermark. In this case, it shall be a configuration of combining several frames. Otherwise there is existed a problem that an electronic watermark signal can not be read out. Further, a case that an electronic watermark signal is recorded in one frame at each several frames can be considered. In this case, there is existed another problem that an electronic watermark signal may disappear from a frame recorded with an electronic watermark signal if a frame not recorded with an electronic watermark signal is extracted.

09597450-05726560  
07



electronic watermark signal detected by the detecting device temporarily, an extracting device for extracting a part of contents data from the original contents data and an inserting device for recording a second electronic watermark signal of which content is equivalent to that of the first electronic watermark signal detected by the detecting device in the contents data extracted by the extracting device.

According to another aspect of the present invention, there provided a recording method of an electronic watermark comprising a step of detecting a first electronic watermark signal from an original contents data inputted, a step of storing the first electronic watermark signal detected in the step of detecting temporarily, a step of extracting a part of contents data from the original contents data and a step of inserting a second electronic watermark signal of which content is equivalent to that of the first electronic watermark signal in the contents data extracted in the step of extracting.

Other object and further features of the present invention will be apparent from the following detailed description when read in conjunction with the accompanying drawings.

5

## BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 shows a block diagram of a recording apparatus of an electronic watermark according to a first embodiment of the present invention.

Fig. 2 shows a block diagram of a recording apparatus of an

Sub  
Q10  
Sub  
Q11

0000250 05726960

electronic watermark according to a second embodiment of the present invention.

Fig. 3 shows a block diagram of an encoding section in a recording apparatus of an electronic watermark according to a third embodiment of the present invention.

Fig. 4 shows a block diagram of a decoding section in a recording apparatus of an electronic watermark according to the third embodiment of the present invention.

Fig. 5 shows a block diagram of a decoding section in a recording apparatus of an electronic watermark according to a fourth embodiment of the present invention.

Fig. 6 shows a block diagram of the MPEG encoder according to the prior art.

Fig. 7 shows a block diagram of the MPEG decoder according to the prior art.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

~~{First Embodiment}~~

Fig. 1 shows a block diagram of a recording apparatus of an electronic watermark according to a first embodiment of the present invention.

In Fig. 1, a recording apparatus comprises a detector 1 of signal, a memory 2 for electronic watermark contents, an extractor 3 of contents signal and an inserter 4 of electronic watermark.

A contents information is inputted into the detector 1 and an









predetermined area.

Further, in a case that a contents data is an audio data and an audio data of a less number of samples than a predetermined number of samples is extracted from an original audio data recorded with a first electronic watermark signal in each predetermined number of samples or throughout the predetermined number of samples, a second electronic watermark signal of which content is equivalent to that of the first electronic watermark signal can be recorded in the extracted audio data, wherein the second electronic watermark is recordable in a less number of samples than the predetermined number of samples.

Furthermore, with assuming that a contents data is other data than picture such as a letter and an audio data, in a case that a contents data of a less number of samples than a predetermined number of samples is extracted from an original contents data recorded with a first electronic watermark signal in each predetermined number of samples or throughout the predetermined number of samples, a second electronic watermark signal of which content is equivalent to that of the first electronic watermark signal can be recorded in the extracted contents data in a less number of samples than that the predetermined number of samples.

~~[Third Embodiment]~~

This embodiment is an application of adopting the MPEG encoder shown in Fig. 6 and the MPEG decoder shown in Fig. 7 in a recording apparatus of an electronic watermark.

Fig. 3 shows a block diagram of an encoding section in a

recording apparatus of an electronic watermark according to a third embodiment of the present invention.

Fig. 4 shows a block diagram of a decoding section in a recording apparatus of an electronic watermark according to the  
5 third embodiment of the present invention.

In Fig. 3, an encoding section of a recording apparatus of an electronic watermark comprises an inserter 11 of an electronic watermark signal and an MPEG encoder 12. As shown in Fig. 3, the inserter 11 receives an intra-coded picture (intra-picture)  
10 location signal from the MPEG encoder 12 and records an electronic watermark signal if an inputted contents information is an intra-picture. Essentially, an intra-picture is distributed with a maximum amount of codes and is coded in picture quality of a highest S/N. Accordingly, it is considered that strong tolerance to  
15 an electronic watermark signal, which is hardly disappeared by a compression encoding. Finally, a compressed contents information is outputted from the MPEG decoder 12.

*Sub  
at 15*  
20

In Fig. 4, a decoding section of the recording apparatus of an electronic watermark comprises an MPEG decoder 13, a detector 1 of signal, a memory 2 for electronic watermark contents, an extractor 3 of contents signal, an inserter 4 of electronic watermark, a decider 5 for judging whether or not an electronic watermark signal is existed and a switch 6.

As shown in Fig. 4, a contents information compressed by the  
25 encoding section shown in Fig. 3 is transmitted to the MPEG decoder 13 and decoded through the MPEG decoding process, and then the compressed contents information becomes an input contents information and transmitted to the detector 1. An

electronic watermark signal is detected from the input contents information by the detector 1, in other words, an electronic watermark signal recorded in an intra-picture is detected. The detected electronic watermark signal (first electronic watermark signal) is temporarily stored in the memory 2. The input contents information is transmitted to the extractor 3 thereafter. A part of a contents signal is extracted from an original contents signal in the extractor 3.

On the other hand, the electronic watermark signal stored temporarily in the memory 2 is transmitted to the inserter 4.

The contents signal extracted from the input contents information by the extractor 3 is judged by the decider 5 whether or not an electronic watermark signal is recorded. A result of judgement is transmitted to the switch. In a case that an electronic watermark signal is recorded, the switch 6 is connected to the decider 5 and the contents signal extracted by the extractor 3 is outputted as it is.

In a case that an electronic watermark signal is not recorded, the switch 6 is connected to the inserter 4. A contents signal recorded by the inserter 4 with a new electronic watermark signal (second electronic watermark signal) of which content is equal to that of a first electronic watermark signal is outputted through the switch 6.

~~[Fourth Embodiment]~~

Fig. 5 shows a block diagram of a decoding section in a recording apparatus of an electronic watermark according to a fourth embodiment of the present invention.

A recording apparatus in this embodiment utilizes a signal, which indicates an intra-picture outputted from an MPEG encoder.

In Fig. 5, a recording apparatus of an electronic watermark  
5 comprises an MPEG decoder 13, a detector 1 of signal, a memory 2 for electronic watermark contents, an extractor 3 of contents signal, an inserter 4 of electronic watermark, a decider 14 for judging a picture type and a switch 16.

As shown in Fig. 5, a contents information compressed by the  
10 encoding section shown in Fig. 3 is transmitted to the MPEG decoder 13. The MPEG decoder 13 transmits a picture-type information contained in the inputted compressed contents information, which is a picture signal of compression encoded by the MPEG system, to the decider 14. A contents signal extracted  
15 by the extractor 3 is judged by the decider 14 whether or not the contents signal is an intra-picture on a basis of the picture-type information. A result of judgment is transmitted to the switch 16. In a case that it is judged as an intra-picture, the switch 16 is connected to the decider 14. The contents signal extracted by the  
20 extractor 3, that is, a picture signal being inserted with an electronic watermark signal and judged as an intra-picture is outputted as it is.

In a case that it is judged as not an intra-picture, the switch  
16 is connected to the inserter 4. In the inserter 4, a new  
25 electronic watermark signal (second electronic watermark signal) of which content is equivalent to that of a first electronic watermark signal supplied by the memory 2 is recorded in the extracted contents signal, that is, a picture signal of not being an

intra-picture. The contents signal recorded with the second electronic watermark signal is outputted through the switch 16. The other blocks shown in Fig. 5, which are not depicted in this embodiment, are the same functions as those of the third  
5 embodiment shown in Fig. 4.

*Sub  
a/b*

The third and fourth embodiments shown in Figs. 3 through 5 disclose that an electronic watermark signal is recorded in an intra-picture by using a characteristic of an intra-picture of which picture quality is most improved while the MPEG compression. In  
10 a case of extracting other picture data than an intra-picture when decoding, a new electronic watermark signal of which content is equivalent to that of an electronic watermark signal originally recorded in the intra-picture is recorded in the picture data to be extracted. Accordingly, an electronic watermark signal can be  
15 recorded efficiently and contents of the electronic watermark signal can be held even though data of a specific part of a contents information, which is compression encoded by the MPEG system, is extracted.

As mentioned above, according to the present invention, an  
20 electronic watermark signal of which content is equivalent to that of a first electronic watermark signal can always be held in an extracted contents data, while extracting the contents data of less amount of information than a predetermined unit of information from an original contents data recorded with the first electronic  
25 watermark signal in each predetermined unit of information or throughout the predetermined unit of information.